

MISC. IMPLEMENTS

TANDEM DISC



SUPERIOR MEDIUM DUTY TANDEM DISC HARROW IS AN IDEAL CHOICE FOR LANDSCAPING, GARDENING, SMALL ACREAGE, OR GENERAL FARM TILLING.

MODEL#	DESCRIPTION	WEIGHT	LIST			
DH30-60C	57	735#	\$1,754			
DH30-60N	60" MEDIUM DUTY TANDEM DISC HARROW NOTCHED BLADES - FRONT & REAR	735#	\$1,754			
DH30-72C	72" MEDIUM DUTY TANDEM DISC HARROW COMBO - NOTCHED FRONT & SMOOTH REAR	815#	\$1,934			
DH30-72N	72" MEDIUM DUTY TANDEM DISC HARROW NOTCHED BLADES - FRONT & REAR	815#	\$1,934			
DH30-84C	84" MEDIUM DUTY TANDEM DISC HARROW COMBO - NOTCHED FRONT & SMOOTH REAR	885#	\$2,053			
DH30-84N	84" MEDIUM DUTY TANDEM DISC HARROW NOTCHED BLADES - FRONT & REAR	885#	\$2,053			

FEATURES:

FRAME AND GANG TUBES ARE CONSTRUCTED OF HEAVY 3" SQUARE TUBING
 AVAILABLE WITH NOTCHED, SMOOTH OR COMBINATION DISC BLADES
 1/2" THICK BEARING HANGERS WITH REINFORCEMENT
 GANG BOLTS ARE 1" SQUARE WITH TRIPLE SEALED, SELF-ALIGNING BALL BEARINGS
 7 1/2" DISC BLADE SPACING ALLOWS THE BLADE TO CUT EVENLY OVER THE GROUND
 FRONT AND REAR GANG ADJUSTABLE WITH 7°, 14° AND 21° SETTINGS
 ALL WELDED UNITS - NO ASSEMBLY REQUIRED
 WE WILL POWDER COAT TO MATCH MOST COMMON TRACTOR COLORS AT NO ADDITIONAL CHARGE!

SPECIFICATIONS	DH30-60	DH30-72	DH30-84
WORKING WIDTH	60"	72"	84"
NUMBER OF BLADES	16	20	24
WEIGHT	735lbs	815lbs	885lbs
HP RATING	35HP MAX	45HP MAX	55HP MAX
HITCH	CAT I, ASAE QUICK HITCH COMPATIBLE		
DISC BLADE SIZE	18"		
DISC BLADE SPACING	7 1/2"		
DISC BLADE TYPE	PLAIN, NOTCHED OR COMBINATION		
FRAME TUBE	3" SQUARE		
BEARING HANGER	3/8" PLATE-REINFORCED		
BEARING TYPE	SELF ALIGNING, SEALED BEARINGS		
GANG TUBE	3" SQUARE		
GANG AXLE	1" SQUARE, HIGH CARBON STEEL		
FRONT/REAR GANG ADJUSTMENT	7, 14, 21 DEGREES WITH ADJUSTMENT HANDLE		

MISC. IMPLEMENTS

LEIGHTWEIGHT LANDSCAPE RAKE



THE **SUPERIOR** LANDSCAPE RAKES ARE EXCELLENT TOOLS FOR SPREADING TOP SOIL, DISTRIBUTING GRAVEL AND REMOVING STICKS AND DEBRIS.

FEATURES:

ADJUSTABLE TO USE IN THE STRAIGHT POSITION OR ANGLED TO THE RIGHT OR LEFT FOR WINDROWING MATERIAL
 AVAILABLE WITH OPTIONAL GAUGE WHEEL - A GREAT AID FOR STABILTY AND LEVELING IN GENERAL GRADING WORK
 POSITION THE RAKES IN REVERSE FOR PUSHING MATERIAL INTO SLOPED POSITION
 FORWARD AND REVERSE SETTINGS AT 18° OR 36°
 HIGH CARBON STEEL TEETH ON 1" SETTINGS
 ALL WELDED UNITS - NO ASSEMBLY REQUIRED
 WE WILL POWDER COAT TO MATCH MOST COMMON TRACTOR COLORS AT NO ADDITIONAL CHARGE!

STANDARD LANDSCAPE RAKE



FEATURES:

FIVE FORWARD AND FIVE REVERSE ANGLE POSITIONS ON ALL MODELS
 OPTIONAL DUAL GAUGE WHEEL KITS ARE AVAILABLE FOR ALL MODELS
 FORMED TINE WITH LOCKABLE TINE SPACING 1" SPACING BETWEEN TINES
 ALL WELDED UNITS - NO ASSEMBLY REQUIRED MAXIMUM ANGLE SETTING OF 45°
 WE WILL POWDER COAT TO MATCH MOST COMMON TRACTOR COLORS AT NO ADDITIONAL CHARGE!

MODEL#	DESCRIPTION	WEIGHT	LIST
LR10-48	48" SUB-COMPACT LANDSCAPE RAKE	145#	\$496
LR10-60	60" SUB-COMPACT LANDSCAPE RAKE	155#	\$565
LR20-60	60" STANDARD DUTY LANDSCAPE RAKE	200#	\$633
LR20-72	72" STANDARD DUTY LANDSCAPE RAKE	220#	\$684
LR20-84	84" STANDARD DUTY LANDSCAPE RAKE	240#	\$736
LR20-96	96" STANDARD DUTY LANDSCAPE RAKE	270#	\$787
LR99-01	GAUGE WHEEL KIT FOR LANDSCAPE RAKE (PAIR)	70#	\$334

SPECIFICATIONS	LR10-48	LR10-60	LR20-60	LR20-72	LR20-84	LR20-96
WORKING WIDTH	48"	60"	60"	72"	84"	95"
WEIGHT	168lbs	178lbs	195lbs	240lbs	270lbs	300lbs
NUMBER OF TINES			30	36	42	48
HITCH	CAT I					
TINE HEIGHT	12"		15"			
TINES	HIGH CARBON STEEL		5/16" X 1" HIGH CARBON STEEL			
HP RATING	30-40HP, 2 OR 4WD		30-60HP, 2 OR 4WD			
BOOM/CROSSBEAM	3" X 3" X 3/16" STEEL TUBING		4" X 4" X 1/4" STEEL TUBING			
MAST	3/16" PLATE					
SWIVEL PLATE	3/8" PLATE		1/2" PLATE			

MISC. IMPLEMENTS

RIPPER BAR



THE **SUPERIOR** RIPPER BAR AERATES SOIL FOR BETTER WATER PENETRATION AND INCREASES GROWTH AND YIELD THROUGH BETTER ROOT DEVELOPMENT.

MODEL#	DESCRIPTION	WEIGHT	LIST
RPB48	48" RIPPER BAR, 4 SHANKS, CAT I	140#	\$411
RPB54	54" RIPPER BAR, 4 SHANKS, CAT I	155#	\$428
RPB60	60" RIPPER BAR, 5 SHANKS, CAT I	175#	\$462
RPB66	66" RIPPER BAR, 6 SHANKS, CAT I	195#	\$496
RPB72	72" RIPPER BAR, 6 SHANKS, CAT I	210#	\$513

FEATURES:

4" X 4" TUBING WITH END CAPS

3/8" SHANK POCKETS FOR ADDED STRENGTH

SHANKS ARE HEAT TREATED WITH REPLACEABLE TIPS

JACK STAND ATTACHED BEHIND THE BAR TO AID IN HOOK-UP

ALL WELDED UNITS - NO ASSEMBLY REQUIRED

WE WILL POWDER COAT TO MATCH MOST COMMON TRACTOR COLORS AT NO ADDITIONAL CHARGE!

SPECIFICATIONS	RPB48	RPB54	RPB60	RPB66	RPB72
WORKING WIDTH	43.5"	46.5"	56"	58"	67.5"
OVERALL WIDTH	48"	54"	60"	66"	72"
APPROX WEIGHT	140lbs	155lbs	175lbs	195lbs	210lbs
SHANKS	4	4	5	6	6
MAIN BEAM	4" x 4" x 1/4" SLOTTED TUBE				
SHANK ADJUSTMENT	MANUAL				
HP RATING	30-40HP MAX				
HITCH	CAT I, ASAE QUICK HITCH COMPATIBLE				
MAST	1/2" X 22" X 6" ALL WELDED				