



FAST AG SOLUTIONS **SPRAYERS**



FAST DESIGNED
BY FARMERS | FOR FARMERS

FAST DESIGNED BY FARMERS | FOR FARMERS

Founded in 1990 by Verlyn Fast, a farmer seeking to increase the productivity of his own operations, FAST's mission is to provide quality products at competitive prices, backed by dependable service. Today, FAST represents farmers and engineers coming together to produce high quality sprayer and liquid fertilizer equipment that is both practical and productive. Our welders, fabricators, assemblers, and painters are skilled craftsmen who take pride in their work.

We realize how important it is for today's farmers to continue to become more efficient and profitable, so our equipment is designed and built to make your job quick, accurate, and safe. Your investment in FAST equipment will pay dividends for years to come.

Our goal at FAST is to make you a life-long customer, one piece of equipment at a time.

100% EMPLOYEE OWNED

In 2015, FAST became a 100% employee-owned company through a merger with WASP, Inc. (now known as FAST Global Solutions, Inc.), based out of Glenwood, MN. This partnership has allowed both companies to diversify and continue to grow by devoting more resources to new product design and innovation as well as having more workforce and capacity available to meet customer demands. Together, both FAST AG and FAST Global are committed to continuing to provide quality, dependable products while also pushing the envelope on new technologies to help increase the bottom line of your farming operation.



QUALITY DESIGN

Over the years FAST has continued to invest in equipment to increase the automation and consistency of our manufacturing process to provide high quality machinery for farmers. Our manufacturing facility currently utilizes flat laser tables, a tube laser, a robotic welding cell, multiple press brakes, and an automated powder coat paint system.



FAST VS. SELF-PROPELLED

MORE CAPACITY, LESS COMPACTION


Today's Ag environment is changing, operating margins are tighter, and pre-emerge spraying is becoming increasingly important. All of which make pull-type and 3-point mounted sprayers a better fit for your operation.


Annual Total Sprayer Cost per Acre Farmed: \$6.23 vs. \$12.15 — \$59,200 over five years!

- 2,000 acre farmer (three passes per year)
- New 120' FAST 9518T – Ultraglide, AutoYaw - \$77,750
- Used 120' Self Propelled 1000 gallon tank - \$225,000
- 50% Depreciation after five years for both
- Tractor is already available
- Tractor Cost of Operation/Depreciation - \$0.78 per acre
- Self-Propelled Fuel - \$0.30 per acre
- Hidden Costs – Additional Drive Train Maintenance

FAST SPRAYERS OFFER A SOLUTION THAT WILL HELP YOU **REDUCE YOUR COSTS** PER ACRE, **BECOME MORE PRODUCTIVE** WITH LARGER TANK CAPACITY, AND **INCREASE YOUR APPLICATION WINDOW** SINCE A TRAILER SPRAYER CAN OPERATE MORE EFFECTIVELY IN WET CONDITIONS.

**CAN YOU
AFFORD
TO LAY OUT AN
ADDITIONAL
\$59,200 OVER
THE NEXT
FIVE YEARS?**



A green John Deere tractor is pulling a yellow FAST hydraulic sprayer with a long boom in a field. The sprayer has a large yellow tank and a long black boom extending to the right. The field is filled with rows of young green plants.

FAST HYDRAULIC AUTOYAW SYSTEM

TAKE THE STRESS OUT OF YOUR BOOM

FAST offers a Hydraulic AutoYaw cushioning system that is controlled through an ISO compatible display (2630/Pro 700,ect.).

This system has sensors that are mounted to the center section and senses at all times what the position of each wing is. If the wing starts moving forward or rearward due to a sudden start, stop, turn, ect., the sensor will detect that and apply hydraulic cushioning through the fold cylinder to bring the boom to a controlled/cushioned stop and also to bring the boom back to its "home" position.

This system helps significantly when there is sudden tractor movements caused by auto-steer, sudden stops, when turning on ends, and also help prevent any "boom walk" that may be experienced with other booms.

This is a very unique system that is offered by FAST and provides benefits that no other trailer or 3-point sprayer can match. The FAST ISO Hydraulic AutoYaw System is standard on all 9500T and 973PT sprayers (120' and 132' booms).

TIMING & SPRAY COVERAGE IS CRITICAL TO **CONTROLLING WEEDS!**

Is spraying 15-20 gallons per acre making you more inefficient?

Producers need to cover acres on a timely basis in order to spray during tighter windows when weeds are still small. We are also making more passes through the field with pre-emerge spraying and up to 3 post-emerge passes. In addition, with more resilient weeds and chemical mixes requiring 15+ gallons per acre, a larger tank will make your operation much more efficient and provide much better weed kill since you can cover more acres on a timely basis!


FAST offers tanks sizes all the way up to 1800 and 2400 gallons with larger single tire, dual, or track capabilities to still provide more flotation than a self-propelled sprayer.

FAST offers industry leading boom ride with FAST's hydraulically accumulated center pivot center section. FAST's industry leading boom ride ensures your booms spray at a consistent height to allow for more consistent chemical coverage and superior weed kill.

Invest in one of the most critical pieces of equipment on your farm that covers the most amount of acres. A high quality sprayer is extremely important with today's more resilient weeds and will boost your yield!

STEERABLE HITCH

FAST offers a Steerable Hitch option that will automatically compensate to stay in your tractor tracks when turning on headlands. This system ties into your ISO display and through the use of rotary sensors and accelerometers automatically monitors the hitch position and detects trailer movements to know when to compensate. This helps significantly reduce the crop damage on your headlands, keeping more bushels in your field, and will leave your fields looking much more consistent.



FAST DESIGNED BY FARMERS | FOR FARMERS

Operators have tested FAST sprayers over hundreds of thousands of acres and we continue to hear the same feedback as operators love the FAST boom ride and short-coupled design. Our equipment is “Designed by Farmers, For Farmers”, and we demonstrate this by focusing on the features that matter most in your operations. For many reasons, trailer and 3-point sprayers are a smart investment: they allow you to utilize a tractor that would otherwise be sitting in your shed, offer tank sizes to fit your needs with small and large size options, and cause less compaction in your fields than self-propelled options.



#1 – Short Coupled Design

All FAST Sprayers are built to be as compact as possible. Our hitch pin to axle length is 3’ to 4’ shorter than some of our competition which gives your FAST sprayer a huge advantage when tracking on side slopes and headlands to minimize crop damage.



#2 – Industry Leading Boom Ride


With more resilient weeds in today’s fields, even spray patterns and consistent boom ride is becoming increasingly important. FAST’s field-proven, hydraulically-accumulated, center-pivot center section isolates the boom from the trailer and dampens any rough terrain. This provides level boom heights and excellent chemical coverage for superior weed kill.



#3 – Operator Friendly Plumbing

One example of FAST products being “Designed by Farmers, For Farmers” is the plumbing layout on all of our sprayers. It’s easy to understand, and because the plumbing system is not covered it’s easy to access. We use the products in our own fields and we know the importance of well laid out plumbing.





#4 – FAST “Stealth” Style Tank

US Patent #7,585,000. A low center of gravity and large trough sloped sump with excellent cleanout will keep the pump primed on long slopes. This tank also allows FAST to achieve its short coupled design along with multiple dual wheel options. Tanks sizes range from 1050-2400 gallons.



#5 – High Crop Clearance

All FAST sprayers are designed to maximize crop clearance with a single reach tongue and high axle heights, to allow for late season spraying with minimal crop damage. FAST is one of the industry’s leaders in crop clearance design.



#6 – FAST Hydraulic AutoYaw Cushioning System

Unique to FAST and standard on all 120’ and 132’ sprayers, this ISO system will provide hydraulic cushioning when a boom moves forward or rearward caused by any type of sudden movement. This removes a significant amount of stress from the boom and results in a more durable, longer lasting design. This is a game-changer on our large boom sprayers.



#7 – High Quality/Resale Value

Built to last with heavy hinge areas and added laminate plates which hold up in the long run. Utilizes automated Powdercoat paint line and Magni coated hardware (1000 hour salt spray) to keep sprayer looking good years down the road. This keeps you running out in the field and a better resale value when it is time to trade.



#8 – Dual Wheel/Track Capability

Increase your flotation and decrease your compaction with many different dual options or CAMSO (formerly Camoplast) 15” track system. This also helps increase your application window and fits well with our 2400 gallon tank. Huge advantage compared to self-propelled sprayers and very important in pre-emerge spraying.



FAST

9600N/TF SERIES SPRAYER

This compact sprayer gives you the flexibility and performance you need. FAST has designed this boom to allow you to stay on your planter tracks and minimize traffic patterns on headlands and field borders. The 90' boom folds to spray at 60' and the 80' boom folds to spray at 40'.

The 60', 66', 88' and 90' booms are offered in a compact 10' center section (9600N). The 80' and 100' booms are offered in a 12' center section (9600TF).

Operators praise the compact design of the unit, which is desirable for field-tracking to minimize crop damage. This, along with FAST's field-proven, industry-leading boom ride and short-coupled trailer, has made this sprayer a favorite among operators.

FAST DESIGNED
BY FARMERS | FOR FARMERS





Short-Coupled Design

The 9600NITF's short-coupled, high clearance trailer, with one of the shortest hitch-pin-to-axle lengths in the industry, provides superior tracking and minimized crop damage.



Industry-Leading Boom Ride

FAST's field-proven, hydraulically-accumulated, center-pivot center section isolates the boom from the trailer and dampens any rough terrain. This provides level boom heights and excellent chemical coverage for weed kill.



Boom Flexibility/ Decrease Traffic Patterns

Minimizing your footprint in the field and keeping consistent traffic patterns helps increase yield. Therefore, FAST has designed its 80' boom to fold and spray at 40' as well as a 90' boom that folds to spray at 60' to help stay on your planter tracks on end rows and field borders.

STANDARD FEATURES

- FAST "Stealth" Tank Design – U.S. Patent # 7,585,000, 1050 or 1350 gallon capacities offers a low center of gravity and a large troughed sloped sump with excellent cleanout which will keep the pump primed on long slopes
- Breakaway with Fore and Aft Movement - Increased durability and lighter weight with DOMEX® steel
- Adjustable Axle Position and Width - All FAST trailer sprayers have an adjustable axle receiver, movable from the middle position forward 9" to further improve tracking, or backward 9" to provide a more stable ride
- 100 Gallon Rinse Tank and Operator Friendly Fill Platform
- Ace Hydraulic 150-206F (60-66') or Ace Hydraulic 205-304F (80-100') pumps standard with an overspeed protection valve
- Powder Coat Paint - FAST's new automated five-stage wash and powder coat paint line provides a consistent process that gives our steel a durable, attractive finish
- Quality in the Details - FAST's commitment to quality shows up in the details. We improve the life of our product by using DOMs and greasable pins in highly corrosive areas, which leads to a longer-lasting, higher-quality product

KEY OPTIONAL FEATURES

- 380/90R46 Tires - Singles or Duals (also offered in 320/90R46 Duals), reduce soil compaction. Spacing options of 62-120", 80-120", and 88-132"
- Electronic Sight Gauge - Provides a more accurate measurement to allow more efficient chemical management (1350 gal tank only)
- Hypro Cleanload Eductor - Quick and easy way to mix chemical
- Electric Fenceline Nozzles – Increase the weed kill on field borders from the convenience of your cab



FAST

9500T SERIES SPRAYERS

The 9500T Series Sprayer gives operators the ability to cover more acres in a shorter amount of time with our truss-style 120' or 132' booms. The round tube truss-style boom incorporates DOMEX® steel in higher stress areas to reduce weight and add strength. It is designed to increase boom life and allow operators to spray at higher speeds.

FAST's Hydraulic AutoYaw system gives the boom hydraulic cushioning on fore and aft movements to significantly reduce boom stress on sudden stops, starts, and turns.

This boom also has the flexibility to fold and spray at 90', with an option to spray at 60' or 66'.

The 9500T Series offers 1800 or 2400 gallon tank capacities with FAST's patented "Stealth" style tank, while still having one of the shortest hitch pin-to-axle lengths in the industry.

FAST DESIGNED
BY FARMERS | FOR FARMERS





FAST Hydraulic AutoYaw Cushioning System

Unique to FAST and standard on all 120' and 132' sprayers, this ISO system will provide hydraulic cushioning when a boom moves forward or rearward caused by any type of sudden movement. This removes a significant amount of stress from the boom and results in a more durable, longer lasting design. This is a game-changer on our large boom sprayers.



Electronic Sight Gauge (Optional)

Utilizes a float that is placed in the absolute center of the tank to give an accurate tank level measurement. Provides a more accurate measurement for efficient chemical management, and more accurate partial loads.



Short-Coupled Design with Large Tank Capacity

The 9500T's short-coupled, high clearance trailer with one of the shortest hitch-pin-to-axle lengths in the industry, provides superior tracking and minimized crop damage while still offering 1800 or 2400 gallon tanks.

STANDARD FEATURES

- FAST "Stealth" Tank Design – U.S. Patent #7,585,000. 1800 or 2400 gallon capacities offer a low center of gravity and a large troughed sloped sump with excellent cleanout which will keep the pump primed on long slopes
- Industry-Leading Boom Ride – FAST's field-proven, hydraulically-accumulated, center-pivot center section isolates the boom from the trailer. This provides level boom heights and excellent chemical coverage for weed kill.
- Breakaway with Fore and Aft Movement – Increased durability and lighter weight with DOMEX® steel
- Adjustable Axle Position and Width – All FAST trailer sprayers have an adjustable axle receiver, movable from the middle position forward 9", to further improve tracking, or backward 9", to provide a more stable ride
- 3" Quick Fill, 100P Flow Meter, and 1-1/2" Motorized Control Valve
- Pump Hydraulic Flow Limiter – Provides over-speed protection
- Quality in the Details – We improve the life of our product by using DOMs and greasable pins in highly corrosive areas, which leads to a longer-lasting, higher-quality product

KEY OPTIONAL FEATURES

- Larger Single Tires or Duals - Multiple options to increase your flotation and reduce soil compaction, such as the 380/90R54 Duals with a 20k - 10 Bolt Hub. Spacing options of 62-120", 80-120", and 88-132"
- 15" CAMSO (Camoplast) Tracks - Increase your flotation and decrease your compaction. This also helps increase your application window and fits well with our 2400 gallon tank.



FAST

9500TF SERIES SPRAYER

The 9500TF Series Sprayer allows operators to spend more time spraying and less time filling with our 1800 or 2400 gallon tank, while still offering one of the shortest hitch pin-to-axle lengths in the industry in this tank size category.

The 9500TF is also designed to allow you to minimize traffic patterns in the field with a 80' boom that folds to spray at 40' and a 90' boom that folds to spray at 60'.

This model also offers boom sizes from 60'-100' with a boom ride that is second to none with FAST's hydraulically accumulated center pivot center section.

FAST DESIGNED
BY FARMERS | FOR FARMERS





Industry-Leading Boom Ride

FAST's field-proven hydraulically-accumulated center-pivot center section isolates the boom from the trailer and dampens any rough terrain. This provides level boom heights and excellent chemical coverage for superior weed kill.



Operator Friendly Plumbing

The plumbing on all FAST Sprayers is simple to understand, and easy to access and operate. FAST understands the needs of today's farmers, and designs products to make the farmer more efficient and profitable.



Compact Transport Length

FAST's Tri-Fold boom design allows you to stay on your planter tracks and also helps decrease transport length. The booms no longer hang beyond the center section which helps give you less liability on the road and is better for storage.

STANDARD FEATURES

- FAST "Stealth" Tank Design – U.S. Patent #7,585,000, 1800 or 2400 gallon capacities offers a low center of gravity and a large troughed sloped sump with excellent cleanout which will keep the pump primed on long slopes
- Breakaway with Fore and Aft Movement
- Tri-Fold Boom Design – 90' boom will fold to 60' and 80' boom will fold to spray at 40'. 100' boom gives a very compact design with short hitch pin-to-axle length compared to other designs on the market.
- Adjustable Axle Position and Width – All FAST trailer sprayers have an adjustable axle receiver, movable from the middle position forward 9", to further improve tracking, or backward 9", to provide a more stable ride
- Dual Wheel Capability – 62-120", 80-120", 88-132"
- 100 Gallon Rinse Tank and Operator Friendly Fill Platform
- Ace Hydraulic 205-304F pump with hydraulic flow limiter to provide overspeed protection, adding longevity to your pump
- Powder Coat Paint – FAST's new automated five-stage wash and powder coat paint line provides a consistent process that gives our steel a durable, attractive finish

KEY OPTIONAL FEATURES

- Larger Single or Dual Tires – Multiple options to reduce soil compaction. Dual spacing options of 62-120", 80-120", and 88-132"
- Electronic Sight Gauge – Provides a more accurate measurement to allow more efficient chemical management
- CAMSO (Camoplast) 15" TTS tracks system – help minimize soil compaction and increase your application window



FAST

TRACK TANKS

FAST Inboard Track Tanks allow you to maximize the use of the equipment you have already invested in your operations.

973PT 3-POINT BOOMS

The 973PT utilizes our 120-132' truss-style boom, to increase boom life while decreasing overall weight.

FAST's Hydraulic AutoYaw system gives the boom hydraulic cushioning on fore and aft movements to significantly reduce boom stress on sudden stops, starts, and turns.


As can be expected from FAST, operators praise the industry-leading boom ride that is driven from our hydraulically accumulated center pivot center section. These booms will allow you to make the same pass through the field with half of the footprint and less opportunity for crop damage, which is extremely beneficial in areas with more hillsides or in smaller fields.

**FAST DESIGNED
BY FARMERS | FOR FARMERS**



Compact Design

These inboard tanks are mounted inside the track. This keeps the tanks from increasing the transport width of the tractor, giving the operator more flexibility and less liability during transport.



ISO Hydraulic Yaw Control

ISO electronically controlled hydraulic boom relief system designed to allow the boom wing fold-cylinder to flex and retract as needed. This dissipates the accelerations of the boom's wings (tractor must be ISO compatible). This system is unique to FAST equipment, and will cushion any abrupt movements to allow for a lighter, longer-lasting boom.

973PT STANDARD FEATURES

- The same FAST field-proven boom design that is used in the trailer sprayers
- Truss style boom utilizing high strength, lighter weight DOMEX® steel incorporated into the design to provide a strong structural boom with decreased overall weight
- Breakaway with Fore and Aft Movement – Increased durability and lighter weight with DOMEX® steel
- Ace 205-304F Hydraulic Pump with hydraulic flow limiter to provide overspeed protection
- Triple Nozzle Bodies
- Adjustable Wing Rest and Parking Stands
- Powder Coat Paint

KEY OPTIONAL FEATURES

- ISO Ready Connection
- Hypro Cleanload Chemical Eductor
- Raven ISO Auto Boom Height Control
- Fenceline Nozzles



Rinse Out System

Track Tanks come with a rinse system that utilizes a sparger tube and rinse balls to spray clean water throughout the tank when switching chemicals to reduce contamination. This, along with the tanks' stainless steel design helps ensure excellent chemical cleanout.

TRACK TANKS

FAST Track Tanks are compatible with both John Deere (1000 gallon capacity) and Challenger (850 gallons) track tractors and give you maximum flexibility to utilize in multiple applications, such as starter fertilizer, side-dressing, and spraying. These tanks are made out of stainless steel with increased life for high durability and excellent cleanout. Operators praise the smooth ride and flexibility obtained from these tractor mounted tanks.

TRACK TANK STANDARD FEATURES

- Excellent Weight Distribution - Optimum ride and maximum flotation
- Sparger Tubes – Full Length, Stainless Steel
- Made from 10 Gauge Stainless Steel
- Stainless Steel Welded in Baffles
- Rubber Mounted on Frame
- External Sight Gauge
- Powder Coat Paint



The logo for FAST, featuring the word "FAST" in a bold, italicized, sans-serif font with a stylized mountain range graphic underneath.

953P SERIES SPRAYERS

The 953P helps minimize tracks in the field and provides a great alternative to a self-propelled sprayer at a fraction of the cost. FAST utilizes a single 500 or 750 gallon tank with FAST's field proven boom design from 60'-100'. This sprayer will be an excellent addition to your operation, especially in tighter fields and in hilly conditions.

This sprayer also works very well to spray field borders with minimal crop damage.



STANDARD FEATURES

- Tri-Fold Boom Design – 80' boom folds to spray at 40' and 90' boom folds to spray at 60' to help minimize traffic patterns while spraying fields borders and headlands
- Ace Hydraulic 150-206F (60-66') or Ace Hydraulic 205-304F (80-100') pumps standard with an overspeed protection valve
- Center Pivot Center Section – provides stable boom ride
- Breakaway with Fore and Aft Movement - Increased durability and lighter weight with DOMEX® steel
- Compact Transport Position – provides great visibility
- 50 Gallon Rinse Tank



Easy Access Plumbing

Similar to all FAST sprayer designs, the 953P has all of its main plumbing controls on one side of the sprayer, is easy to access, and easy to understand.



One Main Tank/More Capacity

Other designs utilize two tanks rather than one. A single tank design provides for better/even cleanout of the tank and the ability to keep your pump primed

more effectively on hillsides. Add a FAST 300 gallon Front Tank to provide even more capacity!


963PTF SERIES SPRAYERS

FAST's 963PTF boom gives you great flexibility to work with both wheel or track tractors, and makes a great combination with our FAST Track Tanks. This 60'-100' boom with a hydraulically accumulated center industry-leading center section will give you superior boom ride and allow your operation to become more efficient and profitable.



Parallel Link System

All of FAST's three point mounted sprayers use the same parallel link system as our trailer sprayers. This gives you maximum boom height adjustability for all stages of crop growth.



ISO Ready Connection

All FAST Sprayers can be configured to run product control through your ISO ready tractor and in-cab display. This gives you the ability to utilize section control and minimize clutter in your cab.



STANDARD FEATURES

- Hydraulically Accumulated Center Pivot Center Section – Isolates boom from the tractor and provides a stable boom ride for superior weed kill
- Tri-Fold Boom Design – 80' boom folds to spray at 40' and 90' boom folds to spray at 60' to help minimize traffic patterns while spraying fields borders and headlands
- Stainless Steel Wet Boom Plumbing – Higher flow rates, better chemical residual cleanout
- Ace Hydraulic 150-206F (60-66') or Ace Hydraulic 205-304F (80-100') pumps standard with an overspeed protection valve
- Parking Stands and Safety Light Kit

FAST

BIG WHEEL 500 & 750 SPRAYERS

These sprayers are an excellent addition to your operations in areas with more hillsides and compact fields, while still receiving the same high level of quality you expect from all FAST products.

Operators can choose from the 500 gallon tank with a 45' boom or a 750 gallon tank with a 60' boom.

As with all FAST sprayers, this trailer is also designed to minimize crop damage with its compact design and make it an operator-friendly sprayer to use.



Valve Tower

A handy valve tower allows the operator to know which valves to turn in an easy-to-operate manner.



Center Pivot Hydraulic Fold Boom

The BW500 and BW750 feature a hydraulic lift with parallel lift arms and a single-acting hydraulic cylinder. This, along with hydraulically-accumulated center section, give a stable boom ride and spray heights up to 51".



STANDARD FEATURES

BW500

- 45' Hydraulic Fold and Hydraulic Wing Tilt Boom
- 500 Gallon Tank
- 12.4 x 24" or 11.2 x 38" Tire Options

BW750

- 60' Hydraulic Fold and Hydraulic Wing Tilt Boom
- 750 Gallon Tank
- 13.6 x 38" Tires
- 50 Gallon Rinse Kit- In-line Filter Kit (3) for Boom feed lines
- 5 Gallon Chem Inductor

SHARED

- Short Coupled Design - Improve Tracking, less crop damage
- High Crop Clearance
- Adjustable Agitation Jets
- Ace 540 PTO pump or Ace 150-206F Hydraulic Pump

UT3P SPRAYERS

The FAST UT3P Sprayer is excellent for spraying in hard-to-reach areas or field corners. It is also ideal for rescue spraying and spraying along fence lines.

Manual Folding Boom sizes are 25', 30', and 40' along with Hydraulic Folding Boom Sizes of 40' and 45' with tank sizes of 250 or 300 gallons. A boomless option is also available for the UT3P sprayer, which utilizes two broadcast nozzles mounted on the back of the tank frame.



STANDARD FEATURES

- Hypro 6500C PTO 540 4 Roller Pump - standard on all UT3P sprayers
- FAST Pasture UT3P Tanks - Offered in either 250 or 300 gallon capacities.
- Ace Hydraulic 75-204 Pump - Optional
- Hypro Boom Extender Nozzles - Boomless Option
- Three Point Mount to Tractor - Category II and II
- Parking Stand and Fork Pockets integrated into the frame - stand on its own
- Safety Light Kit
- Hand Wand
- Powder Coat Paint



Narrow Transport Width

Hauling the FAST UT3P Sprayer down any road is not a problem, as it is designed with a 8' transport width.



Hydraulic or Manual Fold Boom

Choose the best fit for your operation. Manual fold booms come in 25', 30', or 40' options. Hydraulic folding booms utilize two tractor hydraulic outlets and are offered with 40' or 45' boom sizes. Both style booms utilize a breakaway boom the breaks both forward and rearward.



FAST AG SOLUTIONS SPRAYER

S P E C I F I C A T I O N S

MODEL	9600N/TF (60'-100')	9500TF (60'-100')	9500T (120'-132')	953P	BIG WHEEL
Transport Height	10'7" (60') or 11'10" (90')	10'8" (60') or 11'11" (100')	13'3"	N/A (Tractor Dependent)	8'4" (BW500)
Transport Width	10'1" - 60', 66', 90' (N) 12'3" - 80', 100' (TF)	12'3"	12'4"	12'3"	8'1" (BW500)
Transport Length	18'5"	21'6"	23'10"	12'9"	17'6" (BW500)
Transport Weight Empty	7,620 (9613N 90')	8,300 (9518TF 90')	11,860 (9518T 120')	5,620 (90')	3,240 (BW500)
Field Weight Tanks Full	19,780 (9613N 90')	24,090 (9518TF 90')	27,200 (9518T 120')	9,620 (500 Gal 90') 11,880 (750 Gal 90')	8,320 (BW500)
Tank Size Gallons	1050 or 1350	1800 or 2400	1800 or 2400	500 or 750	500 or 750
Boom Sizes	60', 66', 80', 88', 90', 100'	60', 66', 80', 88', 90', 100'	120' or 132'	60', 66', 80', 88', 90', 100'	45' or 60'
Tank Rinse System	100 Gallon Rinse Tank	100 Gallon Rinse Tank	100 Gallon Rinse Tank	50 Gallon Rinse Tank	50 Gallon Rinse Tank
Standard Pump	Ace 150-206F (60', 66') or Ace 205-304F (80' - 100')	Ace 205-304F	Ace 205-304F	Ace 150-206F (60', 66') or Ace 205-304F (80'-100')	Ace 540 PTO
Standard Tires	13.6x38" or 320/90R46	380/90R46 or 480/80R50	380/90R46 or 480/80R50	N/A	12.4x24" or 11.2x38" (BW500) 13.6x38" (BW750)
Dual Wheel Capability	Yes: 60"-120", 80"-120", 88"-132"	Yes: 62"-120", 80"-120", 88"-132"	Yes: 62"-120", 80"-120", 88"-132"	N/A	No
Quick Fill	2"	3"	3"	2"	2"
Hitch-pin-to-axle Length	152"	175"	175"	N/A	144" (BW500)

WINDOM, MN

4130 Commerce Blvd, Windom, MN 56101
toll free 800.772.9279 • p 507.427.3861 • f 507.427.3030

GILMAN, IL

1340 S Crescent, PO Box 236, Gilman, IL 60938
toll free 800.872.8894 • p 815.265.7125 • f 815.265.7130

www.fast-mfg.com

REV: JULY 2016

